



ZP26 “B “ VERSION WITH BRUSHLESS MOTOR !!



ZP26-6B Battery powered. Automatic plastic strapping tool (Max. tension 330 kg)

- “3 Year Warranty” on Brushless Motor and ECU (Electronic Control Unit)
- The most powerful tool for heavy duty strapping.
- Automatic tension, automatic friction weld sealing & cutting. No metal seals required.
- A protection shelter keeps tension & sealing adjustment knobs from undesired touch.
- Ergonomic design and excellent weight distribution reduce hand strength.
- Easy “One-Step” straps inserting.
- Computer controlled operation monitoring system.
- User self-adjustable front & rear strap width guiders assure perfect strap alignment.
- User changeable strap cutting blade and other wearing parts.
- 14.4V 3.0Ah Ni-MH high capacity rechargeable battery
- BOSCH 30 minutes charger.
- Optional hanger reduces operation fatigue.
- Max. strap thickness 1.27mm (0.05”) is allowed. However, a changeover of blade (part no. 2885) is required
- Specifications:

| Model | Battery Charger Voltage | Fits poly strap | Strap Width | | Strap Thickness | | Approx. Tension Range | Sealing Efficiency |
|---------|-------------------------|-----------------|-------------|---------|-----------------|----------|-----------------------|--------------------|
| | | | mm | inch | mm | inch | | |
| ZP26-6B | 115V | PP | 16 | 5/8 | 0.75-1.27 | .029-.05 | 50-140 kg | 85+-5% |
| | 220V | PET | 13-16 | 1/2-5/8 | 0.60-1.27 | .024-.05 | 70-270 kg | |
| ZP26-9B | 230V | PP | 16&19 | 5/8&3/4 | 0.75-1.27 | .029-.05 | 50-140 kg | |
| | 240V | PET | | | 0.65-1.27 | .026-.05 | 80-330 kg | |